

# SLICE

## OF STAINLESS

AN ONI COMPANY



### CERTIFICATION

- AS9120B with ISO 9001:2015

### INDUSTRIES SERVED

- Aerospace
- Medical
- Tool & Die
- Food Processing
- Space
- Oil & Gas
- Electronics
- & Many More!

### SOLUTIONS

- No Minimum Size Orders
- Domestic / DFARS Material
- Same Day Shipping/AOG
- Full Traceability Mill Certifications

## WE ARE

- Dependent—on our customers for our success. We will treat you like family!
- Responsive—offering most quotes within 2 hours and shipping most orders same day.
- Dependable—we have a wide-ranging inventory, and we ship on time!
- Trustworthy—neutral packaging as required.
- Friendly—we love hearing from you!

**PLACE YOUR ORDER ONLINE! [WWW.SLICEOFSTAINLESS.COM](http://WWW.SLICEOFSTAINLESS.COM)**

# SLICE OF STAINLESS PRODUCTS

STAINLESS	SPECIFICATIONS	SHEET
15-5 PH	AMS 5862, ASTM A693, GE S-400/S1000	0.025, 0.032, 0.040, 0.050, 0.063, 0.071, 0.080, 0.090, 0.100, 0.125
17-4 PH	AMS 5604, ASTM A693, ASTM F899, GE S-400/S1000	0.032, 0.040, 0.050, 0.063, 0.080, 0.090, 0.100, 0.125, 0.190, 0.250
17-7 PH	AMS 5528, ASTM A693, GE S-400/S1000	0.016, 0.020, 0.025, 0.032, 0.040, 0.050, 0.063, 0.071, 0.080, 0.090, 0.105, 0.125, 0.160, 0.1875
301 ANN	AMS 5901, ASTM A240, ASTM A666, ASTM A480	0.020, 0.025, 0.032, 0.040, 0.050, 0.063, 0.080
301 QH	AMS 5517, ASTM A666	0.012, 0.016, 0.020, 0.025, 0.032, 0.035, 0.040, 0.050, 0.063, 0.071, 0.080, 0.090, 0.100, 0.125
301 HH	AMS 5518, ASTM A666	0.012, 0.016, 0.020, 0.025, 0.032, 0.035, 0.040, 0.050, 0.063, 0.080, 0.090, 0.100, 0.125
301 FH	AMS 5519, ASTM A666	0.016, 0.020, 0.025, 0.032, 0.040, 0.050, 0.063
302	AMS 5516, AMS 5513, AMS 5511, ASTM A666	0.016, 0.020, 0.025, 0.031, 0.035, 0.040, 0.050, 0.063, 0.080, 0.090, 0.105, 0.125
304	AMS 5513, AMS 5511, AMS 5513, AMS 5516, ASTM A240, ASTM A666	0.016, 0.020, 0.025, 0.031, 0.035, 0.040, 0.048, 0.050, 0.059, 0.063, 0.071, 0.080, 0.090, 0.100, 0.105, 0.115, 0.125, 0.132, 0.160, 0.185, 0.250
304 L	AMS 5513, AMS 5511, AMS 5513, AMS 5516, ASTM A240, ASTM A666	0.016, 0.020, 0.025, 0.031, 0.035, 0.040, 0.048, 0.050, 0.059, 0.063, 0.071, 0.080, 0.090, 0.100, 0.105, 0.115, 0.125, 0.132, 0.160, 0.185, 0.250
310	AMS 5521, ASTM A240	0.024, 0.030, 0.035, 0.048, 0.060, 0.075, 0.102, 0.120
316	AMS 5524, AMS 5507, ASTM A666, ASTM A240	0.018, 0.025, 0.028, 0.035, 0.040, 0.048, 0.058, 0.073, 0.090, 0.105, 0.118, 0.134, 0.160, 0.182, 0.250
316L	AMS 5524, AMS 5507, ASTM A666, ASTM A240	0.018, 0.025, 0.028, 0.035, 0.040, 0.048, 0.058, 0.073, 0.090, 0.105, 0.118, 0.134, 0.160, 0.182, 0.250
321	AMS 5510, ASTM A240, ASTM A480, GE S-400/S1000	0.016, 0.020, 0.025, 0.032, 0.035, 0.040, 0.050, 0.063, 0.080, 0.090, 0.105, 0.125, 0.135, 0.1875, 0.250
347	AMS 5512, ASTM A240, ASTM A262, GE S-400/S1000	0.020, 0.025, 0.031, 0.040, 0.050, 0.063, 0.080, 0.090, 0.125, 0.1875, 0.250
410	AMS 5504, ASTM A240, ASTM F899	0.020, 0.025, 0.031, 0.035, 0.040, 0.050, 0.063, 0.078, 0.090, 0.102, 0.125, 0.132, 0.187
430	AMS 5503, ASTM A240, ASTM A480	0.024, 0.030, 0.035, 0.048, 0.060, 0.100

NICKEL	SPECIFICATIONS	SHEET
625	AMS 5599, ASTM B443, GE S-400/S1000	0.016, 0.020, 0.025, 0.031, 0.035, 0.040, 0.050, 0.061, 0.078, 0.090, 0.100, 0.125
718	AMS 5596, GE S-400/S1000	0.020, 0.025, 0.032, 0.035, 0.040, 0.050, 0.063, 0.071, 0.080, 0.090, 0.100, 0.125
A-286	AMS 5525, GE S-400/S1000	0.025, 0.030, 0.040, 0.050, 0.063, 0.071, 0.080, 0.125

TITANIUM	SPECIFICATIONS	SHEET
TI-6AL-4V	AMS 4911, ASTM F 1472, ASTM B 265 GR 5	0.012 - 0.125

## THICKNESS RANGES

US GAUGE	DECIMAL	AMS 2242 (+/-)	US GAUGE	DECIMAL	AMS 2242 (+/-)
7	.1875	.012	19	.043	.004
8	.172	.012	20	.037	.004
9	.156	.012	21	.034	.004
10	.140	.010	22	.031	.004
11	.125	.008	23	.028	.004
12	.109	.007	24	.025	.003
13	.093	.006	25	.022	.003
14	.078	.005	26	.019	.003
15	.070	.005	27	.017	.003
16	.063	.005	28	.015	.002
17	.056	.004	29	.014	.002
18	.050	.004			